

SHARK KAC

Product Description

Name : KAC
 Type : Dry Sanding
 Backing : Cwt-Special Kraft Paper
 Bonding : Resin over Resin
 Grain : Aluminium Oxide
 Coating : Semi Open Coat
 Shape : Sheet



Available Grit					
0	1	2	3	4	5
•	•	•	•	•	•

Print 0 = Grit No 240
 Print 1 = Grit No 180
 Print 2 = Grit No 150
 Print 3 = Grit No 120
 Print 4 = Grit No 100
 Print 5 = Grit No 80

Product Features

- Rapid sanding performance.
- Excellent durability and toughness backing paper.
- Provide high stock removal.
- Applicable in wall putty sanding.
- Long lasting sanding ability.

Applications

Workpieces

- Wood
- Furniture
- Sealer
- Wall putty

Available Sander / Grinder

- Hand Sanding
- Orbital Sander

Recommendations

- Select grit number of abrasive paper suitable to the sanding surface

Application	Grit No.
• Wall Putty	5-0
• Cutting down Wood surface	5-2
• Surface Condition	1-0
• Primer, Sealer	0

Packaging Size

Grit no.	Sheet/ Sleeve	Sleeve/ Carton	Sheet/ Carton
0-5	60	10	600

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment