

TECHNICAL DATA SHEET

TOA EXTRA PRO

Product Description

Name : TOA EXTRA PRO Type : Dry Sanding

Backing : Bwt-Latex Strong Flex Paper

Bonding : High Performance Synthesized Resin

Grain : Premium Heat-Treated Aluminium Oxide

Coating : Open Coat Shape : Sheet, Roll



Available Grit

40	09	80	100	120	150	180	220	240	280	320	360	400	200	009	800	1000	1200	1500	2000
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Polishing Method







Product Features

- High performance cutting and sanding ability
- · Excellent flexibility
- · Working faster and premium quality
- Can be used both by hand sanding, sanding pad and orbital sander
- Excellent anti-clogging from sanding dust
- · Long lasting sanding ability
- · Increase productivity

Applications

Workpieces

- Wooden paint and lacquer sanding sealer
- Hard wood and soft wood
- Furniture
- Putty / Filler

Packaging Size

	Package Size of Sheet						
Grit	(TOA Extra Pro 230 x 280mm)						
	Sheet/Sleeve	Sleeve/Cartor					
80-180	100	5					
220-1500	100	10					

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Recommendations

• Select grit number suitable to the sanding surface

Application	Grit		
Cutting down wood/putty surface	80-150		
Surface condition	180-240		
Primer, Sealer	280-320		
Topcoat, Laquer	360-600		
Finishing	800-1500		

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment